www.DataSheet4U.com

IXYS


Advance Technical Information

GigaMOS™ Power MOSFET


IXFN180N25T

V_{DSS} = 250V
I_{D25} = 155A
$R_{DS(on)}$ ≤ 12.9mΩ
t_{rr} ≤ 200ns

N-Channel Enhancement Mode
Avalanche Rated
Fast Intrinsic Diode



miniBLOC, SOT-227
E153432



G = Gate D = Drain
S = Source

Either Source Terminal S can be used as the Source Terminal or the Kelvin Source (Gate Return) Terminal.

Symbol	Test Conditions		Maximum Ratings	
V_{DSS}	T_J = 25°C to 150°C		250	V
V_{DGR}	T_J = 25°C to 150°C, R_{GS} = 1MΩ		250	V
V_{GSS}	Continuous		±20	V
V_{GSM}	Transient		±30	V
I_{D25}	T_C = 25°C		164	A
I_{DM}	T_C = 25°C, Pulse Width Limited by T_{JM}		500	A
I_A	T_C = 25°C		40	A
E_{AS}	T_C = 25°C		3	J
dV/dt	$I_S \le I_{DM}$, $V_{DD} \le V_{DSS}$, $T_J \le 150°C$		20	V/ns
P_D	T_C = 25°C		900	W
T_J			-55 ... +150	°C
T_{JM}			150	°C
T_{stg}			-55 ... +150	°C
T_L	1.6mm (0.062 in.) from Case for 10s		300	°C
T_{SOLD}	Plastic Body for 10s		260	°C
V_{ISOL}	50/60 Hz, RMS	t = 1 minute	2500	V~
	$I_{ISOL} \le$ 1mA	t = 1 second	3000	V~
M_d	Mounting Torque		1.5/13	Nm/lb.in.
	Terminal Connection Torque		1.3/11.5	Nm/lb.in.
Weight			30	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{DSS}	V_{GS} = 0V, I_D = 3mA	250			V
$V_{GS(th)}$	$V_{DS} = V_{GS}$, I_D = 8mA	2.5		5.0	V
I_{GSS}	V_{GS} = ±20V, V_{DS} = 0V			±200	nA
I_{DSS}	$V_{DS} = V_{DSS}$, V_{GS} = 0V			50	μA
	T_J = 125°C			3	mA
$R_{DS(on)}$	V_{GS} = 10V, I_D = 60A, Note 1			12.9	mΩ

Features

- International Standard Package
- miniBLOC, with Aluminium Nitride Isolation
- Isolation voltage 2500 V~
- High Current Handling Capability
- Fast Intrinsic Diode
- Avalanche Rated
- Low $R_{DS(on)}$

Advantages

- Easy to Mount
- Space Savings
- High Power Density

Applications

- DC-DC Converters
- Battery Chargers
- Switched-Mode and Resonant-Mode Power Supplies
- DC Choppers
- AC Motor Drives
- Uninterruptible Power Supplies
- High Speed Power Switching Applications


© 2009 IXYS CORPORATION, All Rights Reserved

www.DataSheet4U.com

www.DataSheet4U.com

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	V_{DS} = 10V, I_D = 60A, Note 1	100	160		S
C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		28		nF
C_{oss}			2050		pF
C_{rss}			158		pF
$t_{d(on)}$	**Resistive Switching Times**		37		ns
t_r	V_{GS} = 15V, V_{DS} = 0.5 • V_{DSS}, I_D = 90A		33		ns
$t_{d(off)}$	R_G = 1Ω (External)		100		ns
t_f			28		ns
$Q_{g(on)}$	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 90A		345		nC
Q_{gs}			122		nC
Q_{gd}			70		nC
R_{thJC}				0.138	°C/W
R_{thCS}			0.05		°C/W

SOT-227B (IXFN) Outline



(M4 screws (4x) supplied)

SYM	INCHES MIN	INCHES MAX	MILLIMETERS MIN	MILLIMETERS MAX
A	1.240	1.255	31.50	31.88
B	.307	.323	7.80	8.20
C	.161	.169	4.09	4.29
D	.161	.169	4.09	4.29
E	.161	.169	4.09	4.29
F	.587	.595	14.91	15.11
G	1.186	1.193	30.12	30.30
H	1.496	1.505	38.00	38.23
J	.460	.481	11.68	12.22
K	.351	.378	8.92	9.60
L	.030	.033	0.76	0.84
M	.496	.506	12.60	12.85
N	.990	1.001	25.15	25.42
O	.078	.084	1.98	2.13
P	.195	.235	4.95	5.97
Q	1.045	1.059	26.54	26.90
R	.155	.174	3.94	4.42
S	.186	.191	4.72	4.85
T	.968	.987	24.59	25.07
U	-.002	.004	-0.05	0.1

Source-Drain Diode

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
I_S	V_{GS} = 0V			180	A
I_{SM}	Repetitive, Pulse Width Limited by T_{JM}			720	A
V_{SD}	I_F = 60A, V_{GS} = 0V, Note 1			1.3	V
t_{rr}	I_F = 90A, V_{GS} = 0V			200	ns
Q_{RM}	-di/dt = 100A/µs		0.77		µC
I_{RM}	V_R = 75V		11		A

Note 1: Pulse Test, t ≤ 300µs; Duty Cycle, d ≤ 2%.

ADVANCE TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,850,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123 B1 6,306,728 B1 6,404,065 B1 6,534,343 6,583,505 6,683,344 6,710,405 B2 6,710,463 6,727,585 6,759,692 6,771,478 B2 7,005,734 B2 7,063,975 B2 7,071,537 7,157,338B2

www.DataSheet4U.com

www.DataSheet4U.com

Fig. 1. Output Characteristics @ 25ºC




Fig. 2. Extended Output Characteristics @ 25ºC




Fig. 3. Output Characteristics @ 125ºC




Fig. 4. $R_{DS(on)}$ Normalized to I_D = 90A Value vs. Junction Temperature




Fig. 5. $R_{DS(on)}$ Normalized to I_D = 90A Value vs. Drain Current





Fig. 6. Maximum Drain Current vs. Case Temperature



© 2009 IXYS CORPORATION, All Rights Reserved

www.DataSheet4U.com

www.DataSheet4U.com

Fig. 7. Input Admittance




Fig. 8. Transconductance




Fig. 9. Forward Voltage Drop of Intrinsic Diode




Fig. 10. Gate Charge




Fig. 11. Capacitance






Fig. 12. Forward-Bias Safe Operating Area



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

www.DataSheet4U.com

Fig. 13. Maximum Transient Thermal Impedance



© 2009 IXYS CORPORATION, All Rights Reserved

www.DataSheet4U.com