

35.0

REF

Ø 30.9

INTERFACIAL SEAL

3

RJ45 MODULAR PLUG

COUPLING RING

ZINC, TRIVALENT CHROMATE

(59.9)

21.0

12

24.3

HOUSING

ZINC, TRIVALENT CHROMATE

DOME NUT

2

ZINC, TRIVALENT CHROMATE

SCALE 2:1

1. CABLE DIAMETER RANGE: Ø4.5 - Ø6.9

2 36.9 IN-LBS TORQUE RECOMMENDED FOR DOME NUT.

3 INTERFACIAL SEAL IS SECURED TO HOUSING WITH ADHESIVE.

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION
IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION
SHOULD BE CONTACTED FOR THE LATEST REVISION.

DIMENSIONS:

mm

0

PLC

±1.0

1

PLC

±0.2

2

PLC

±0.10

3

PLC

±0.000

4

PLC

±0.0000

ANGLES

±1°

FINISH

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0

PLC

±1.0

1

PLC

±0.2

2

PLC

±0.10

3

PLC

±0.000

4

PLC

±0.0000

ANGLES

±1°

FINISH

DWN

S. WELDON

26MAR2008

CHK

C. HERTZLER

26MAR2008

APVD

C. HERTZLER

26MAR2008

PRODUCT SPEC

108-2198

APPLICATION SPEC

114-13136

WEIGHT

-

CUSTOMER DRAWING

Tyco Electronics

Tyco Electronics

Harrisburg, PA 17105-3608

NAME

PLUG KIT, UNSHIELDED,
INDUSTRIAL CIRCULAR ETHERNET
CONNECTOR

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A2

00779

C-2008611

-

SCALE

3:1

SHEET

OF

REV

1

www.DataSheet4U.com