

## FEATURES

- \* Ideal for surface mounted applications
- \* Low switching noise
- \* Low forward voltage drop
- \* High current capability
- \* High switching capability
- \* High reliability
- \* High surge capability
- \* RoHS product for packing code suffix "G",  
Halogen free product for packing code suffix "H".

## MECHANICAL DATA



Case: Molded plastic, DO-214AB(SMC)

Epoxy: UL 94V-O rate flame retardant

Lead:MIL-STD-202E method 208C guaranteed

Mounting position: Any

Weight: Approximated 0.231 gram



Dimensions in inches and (millimeters)

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

RATINGS	SYMBOL	SK32C	SK33C	SK34C	SK35C	SK36C	SK38C	SK310C	SK315C	SK320C	UNIT
Marking Code		SK32C	SK33C	SK34C	SK35C	SK36C	SK38C	SK310C	SK315C	SK320C	
Maximum Recurrent Peak Reverse Voltage	VRRM	20	30	40	50	60	80	100	150	200	Volts
Maximum RMS Voltage	VRMS	14	21	28	35	42	56	70	105	140	Volts
Maximum DC Blocking Voltage	VDC	20	30	40	50	60	80	100	150	200	Volts
Maximum Average Forward Rectified Current	IO	3.0									Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	80.0									Amps
Typical Thermal Resistance (Note 2)	ROJC	30									°C/W
Typical Junction Capacitance (Note 1)	CJ	180			150		110		100	80	pF
Operating Temperature Range	TJ	-55 to +125							-55 to +150		°C
Storage Temperature Range	TSTG	-55 to +150									°C

CHARACTERISTICS		SYMBOL	SK32C	SK33C	SK34C	SK35C	SK36C	SK38C	SK310C	SK315C	SK320C	UNIT	
Maximum Forward Voltage at 3.0A DC		V <sub>F</sub>	0.55			0.70		0.85		0.87	0.90	Volts	
Maximum Average Reverse Current at	@T <sub>c</sub> =25°C	I <sub>R</sub>	0.5										mAmps
Rated DC Blocking Voltage	@T <sub>c</sub> =100°C		20										

### NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- Thermal Resistance From Junction to Case.

## RATING AND CHARACTERISTIC CURVES

FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2-TYPICAL FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS

