


Surface Mount Schottky Barrier Rectifier

Package Outline Dimensions (millimeters)



SMC (DO-214AB)		
Dim.	Min.	Max.
A	6.60	7.11
B	5.59	6.22
C	2.75	3.18
D	0.15	0.31
E	7.75	8.13
F	-----	0.20
G	2.00	2.50
H	0.76	1.52
All Dimensions in millimeter		

Features

- High Current Capability
- Low Switching Noise
- High Surge Capability
- Low Power Loss & High Efficiency
- Guard Ring Protection
- Pd-free lead plating & Halogen-free part

Mechanical

- Molded Plastic Low profile SMC (DO-214AB)
- Plastic materials used carries underwriters laboratory flammability classification 94V-0
- Lead Temperature for Soldering Purposes : 265°C Max. for 10 Seconds
- Device Weight : 0.007 ounces (0.226 grams)

Maximum Ratings & Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	SK310C	SK315C	SK320C	Units
Marking Code		SK310	SK315	SK320	
DC Blocking Voltage	V _{RM}	100	150	200	Volts
Working Peak Reverse Voltage	V _{RWM}	70	105	140	
Peak Repetitive Reverse Voltage	V _{RRM}	100	150	200	
Average Rectified Forward Current (Rated VR-20Khz Square Wave) - 50% duty cycle	I _{F(AV)}	3			Amps
Non-Repetitive Peak Forward Surge Current (Surge applied at rated load conditions half wave, single phase, 60Hz)	I _{FSM}	80			Amps
Instantaneous Forward Voltage I _F = 3A , T _A = 25°C	V _F	0.85	0.87	0.9	Volts
Instantaneous Reverse Current V _R = V _{RRM} , T _A = 25°C	I _R	0.5			mA
V _R = V _{RRM} , T _A = 100°C		20.0			
Total Capacitance V _R = 4V , f = 1MHz	C _T	400			pF

NOTE : 1.FR-4 PCB, 2 oz Copper. Minimum recommended pad layout

2.Polyimide PCB, 2 oz Copper. Cathode pad dimensions 18.8x14.4mm , Anode pad dimensions 5.6x14.4mm

Thermal Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Units
Maximum Thermal Resistance Junction to Terminal	$R\theta_{JT}$	10	$^\circ\text{C} / \text{W}$
Operating & Storage Junction Temperature	T_J	150	$^\circ\text{C}$
	T_{STG}	- 65 to +150	


Ratings and Characteristics Curves ($T_A = 25^\circ\text{C}$ unless otherwise specified)


Figure 1: Current Derating Curves




Figure 2: Peak Forward Surge Current




Figure 3: Typical Forward Characteristics





Figure 4: Typical Reverse Characteristics

Suggested Pad Layout




SMC (DO-214AB)	
Symbol	Dimensions
A	3.30
B	2.50
C	4.40
All Dimensions in millimeter	

Ordering information

Part Number	Package	Delivery mode
SK310C THRU SK320C	SMC (DO-214AB)	3,000 pieces / 13" Reel

Tape and Reel Dimensions (millimeters)

Surface Mount Device are packed in accordance with EIA standard RS-481-D and specification.



Item	Symbol	Dimensions (mm)
		SMC (DO-214AB)
Carrier width	A	6.15 ± 0.1
Carrier length	B	8.2 ± 0.1
Carrier depth	C	2.7 ± 0.1
Sprocket hole	d	1.5 ± 0.1
Reel outside diameter	D	330.0 ± 1.0
Reel inner diameter	D1	72.0 ± 1.0
Feed hole diameter	D2	13.0 ± 1.0
Stocket hole position	E	1.75 ± 0.1
Punch hole position	F	5.5 ± 0.1
Punch hole pitch	P	8.0 ± 0.1
Sprocket hole pitch	P0	4.0 ± 0.1
Totall tape thickness	T	0.3 ± 0.1
Tape width	W	16.0 ± 0.3
Reel width	W1	22.0 ± 1.5

Disclaimer

All product specifications and data are subject to change without notice.

Sooner Power Semiconductor Co. Ltd., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "SPS"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

SPS disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify SPS's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of SPS.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling SPS products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify SPS for any damages arising or resulting from such use or sales. Please contact authorized SPS personnel to obtain written terms and conditions regarding products designed for such applications.

Products names and markings noted herein may be trademarks of their respective owners.